

Product Code:

# 7813

# 4-TAKT MOTORBIKE

## Synthetic 4-stroke Engine Oil

Meets the requirements:

SAE 10W-30, API SN, JASO MA/MA2, HONDA,  
HUSABERG, KAWASAKI, SUZUKI, YAMAHA

An innovative synthetic ester-containing engine oil for 4-stroke high-load engines of motorcycles, pit bikes, motards, etc. for off-road (enduro, motocross, trials, etc.) and highway (stuntriding, supermoto, etc.) driving under extreme loads. It was designed for a guaranteed protection of the engine and the durability of the gearbox.

### Product Characteristics:

Test	Method	Unit	Result
Color	visual		RED
Dynamic viscosity at -25 °C	D 5293	[cP](mPas)	5028
Density at 15 °C	D 1298	kg/m <sup>3</sup>	870
Viscosity at 40 °C	D 445	CSt	68.35
Viscosity at 100 °C	D 445	CSt	10.48
Viscosity index	D 2270		141
Flash point	D 92	°C	220
Total base no.	D 2896	mgKOH/g	8.40
Pour point	D 97	°C	-38
Ignition temperature			350
Mechanical impurities	D 2273	%	-

Volume:

1L MN7813-1



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, [info@sct-germany.de](mailto:info@sct-germany.de), tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®